

Profile FOLED-50-BOK

Ref. A57945



- Installation of lighting and stretch films to walls
- High lumen output
- Mounting to 12,5 mm - 0.49" drywall
- Non visible aluminum elements
- Line of light flush with the surface

APPLICATION

- lighting recessed in surfaces made of stretch film and in drywall

MOUNTING


- to the surface, using properly selected screws
- can be easily connected into runs and systems

ADDITIONAL INFORMATION

- the profile has grooves for the attachment of the hooks from the stretch film
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING

1:2



TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver non anodized
Possible fixture shapes	linear, polygonal
Width	74.6 mm
Height	45.5 mm
LED gluing width A	10 mm
LED gluing width B	10 mm
LED gluing width C	10 mm
Number of LED strips A (8 mm wide)	1
Number of LED strips B (8 mm wide)	1
Number of LED strips C (8 mm wide)	1
Width of the glow	51 mm
Max power of a single KLUŚ LED strip	24 W/m
Possibility of obtaining a line of light	yes
Building type	Commercial, Retail, Entertainment/ Arts, HoReCa object

Length	Ref
1000 mm	A0A57945N_1
2005 mm	A0A57945N_2
3010 mm	A0A57945N_3


Facility zone

office, conference room,
communication routes and
corridors


SAMPLE PROJECTS



RELATED ACCESSORIES > COVERS

NAME	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
FOLED	 PMMA	79 %	satin	B17171S

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
FOLED-50-W	 PMMA	<input type="checkbox"/> white	C24294C02

RELATED ACCESSORIES > RELATED LED > CRI 95+




K-CR-0480-24
K-CR-0480-24


K-CR-0960-24
K-CR-0960-24

K-CR-1440-24
K-CR-1440-24


RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY




K-HE-0480-HD-24
K-HEHD-0480-24



K-HE-0960-HD-24
K-HEHD-0960-24



K-HE-1440-HD-24
K-HEHD-1440-24



K-HE-1920-HD-24
K-HEHD-1920-24



K-VHE-0480-24
K-VHE-0480-24



K-VHE-0960-24
K-VHE-0960-24



K-VHE-1440-24
K-VHE-1440-24


RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT



K-RGB-0700-24
K-RGB-0700-24



K-RGB-1200-24
K-RGB-1200-24




K-RGBW-1530-24
K-RGBW-1530-24




K-1920-120-RGB-24
K-RGB-1920-120-24

RELATED ACCESSORIES > RELATED LED > WHITE MONO




K-HD-0480-24
K-HD-0480-24



K-HD-0960-24
K-HD-0960-24



K-HD-1440-24
K-HD-1440-24



K-0480-24
K-0480-24




K-0530-HD-24
K-HD-0530-24

Profile FOLED-50-BOK


Ref. A57945




K-0960-24
K-0960-24




K-1220-24
K-1220-24



K-1275-24
K-1275-24



K-1440-24
K-1440-24



K-1910-HD-24
K-HD-1910-24



K-2300-24
K-2300-24



K-2400-24
K-2400-24


RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONNECTORS




CONNECTOR
ZM-NA-90
42723



CONNECTOR
ZM-NA-120
C28242N00



CONNECTOR
ZM-NA-PION-135
42727




CONNECTOR
ZM-X60-G
42332



CONNECTOR
ZM-X90-G
42334



CONNECTOR
ZM-Y120-G
42336



CONNECTOR
ZM-NA-PION-120
42321



CONNECTOR
ZM-90
C28072N00



CONNECTOR
ZM-PION-120
C28087N00



CONNECTOR
ZM-PION-135
C28088N00

Profile FOLED-50-BOK

Ref. A57945



CONNECTOR
ZM-PION-45
C28084N00



CONNECTOR
ZM-PION-60
C28085N00



CONNECTOR
ZM-T45
C28076N00



CONNECTOR
ZM-T60
C28077N00



CONNECTOR
ZM-T90
C28078N00



CONNECTOR
ZM-X60
C28080N00



CONNECTOR
ZM-X90
C28081N00



CONNECTOR
ZM-Y120
C28082N00

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER



GLAND
6x1,2
C24517C07