

Profile KRAV-05IN

Ref. A18045

Ref. arch 18045



- Backlight of transparent panels
- Supported panel thicknesses: 11,9-13,5 mm - 0.47-0.53"

APPLICATION

- decorative edge illumination for transparent panels


MOUNTING

- to the edge of the panel, using dedicated double-sided adhesive tape

ADDITIONAL INFORMATION

- the profile has a decorative function, it is not a construction profile
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	aluminum
Color	silver anodized
Possible fixture IP	20
Possible fixture shapes	linear
Profile cross-section	rectangular
Width	16.9 mm
Height	28 mm
LED gluing width A	11 mm
Number of LED strips A (8 mm wide)	1
Building type	Entertainment/ Arts, Retail, HoReCa object
Facility zone	furniture, shop windows and exhibition, advertising / POS
Wire out back of extrusion	yes

Length	Ref
1000 mm	A18045A_1 18045ANODA_1
2005 mm	A18045A_2 18045ANODA_2
3010 mm	A18045A_3 18045ANODA_3

Profile KRAV-05IN



Ref. A18045

Ref. arch 18045




SAMPLE PROJECTS



RELATED ACCESSORIES > RELATED END CAPS

NAME	MATERIAL	COLOR	REF.
KRAV-05IN	 ABS	 gray	C24308C02 24308

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT

 K-RGB-1200-24V K-RGB-1200-24 Ref. arch K-RGB-1200-24V	 K-1200-RGB+27/65-24V K-RGB27/65-1200-24 Ref. arch K-1200-RGB+27/65-24V	 K-RGB-0700-24V K-RGB-700-24V Ref. arch K-RGB-0700-24V
--	--	---

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER



GLAND
6,4x1,6
C24518C07
Ref. arch 00802Lo