

Profile KRAV-810

Ref. A18016AZM

Ref. arch 18016



- Backlight of transparent panels
- Supported panel thicknesses: 8-10 mm - 0.31-0.39"

APPLICATION

- decorative edge illumination for transparent panels


MOUNTING

- to the edge of the panel, using dedicated double-sided adhesive tape

ADDITIONAL INFORMATION

- the profile has a decorative function, it is not a construction profile
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver anodized
Possible fixture IP	20
Possible fixture shapes	linear
Profile cross-section	rectangular
Width	14 mm
Height	25 mm
LED gluing width A	8 mm
Number of LED strips A (8 mm wide)	1
Building type	Entertainment/ Arts, Retail, HoReCa object
Facility zone	furniture, shop windows and exhibition, advertising / POS
Wire out back of extrusion	yes

Length	Ref
1000 mm	A18016AZM_1 18016ANODAZM_1
2005 mm	A18016AZM_2 18016ANODAZM_2
3010 mm	A18016AZM_3 18016ANODAZM_3

Profile KRAV-810

Ref. A18016AZM

Ref. arch 18016


SAMPLE PROJECTS



RELATED ACCESSORIES > RELATED END CAPS

NAME	MATERIAL	COLOR	REF.
KRAV-810	PP	gray	C28000C02 24028


RELATED ACCESSORIES > RELATED LED



K-1210-12V
K-1210-12
Ref. arch K-1210-12V




K-1275-12V
K-1275-12
Ref. arch K-1275-12V




WP-K-1220-12V
KWP-1220-12
Ref. arch WP-K-1220-12V




WP-K-1220-IP65-12V
_błąd
Ref. arch WP-K-1220-IP65-12V



K-1275-RGB-12V
K-RGB-1275-12
Ref. arch K-1275-RGB-12V



K-0700-120-RGB-24V
_błąd
Ref. arch K-0700-120-RGB-24V




K-1200-120-RGB-24V
_błąd
Ref. arch K-1200-120-RGB-24V

Profile KRAV-810

Ref. A18016AZM

Ref. arch 18016


RELATED ACCESSORIES > RELATED LED > CRI 95+



K-CR-1210-24V
K-CR-1210-24
Ref. arch K-CR-1210-24V




K-CR-1220-24V
K-CR-1220-24
Ref. arch K-CR-1220-24V




K-CR-1275-24V
K-CR-1275-24
Ref. arch K-CR-1275-24V

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY




K-HE-0480-HD-24V
K-HEHD-0480-24
Ref. arch K-HE-0480-HD-24V



K-HE-0960-HD-24V
K-HEHD-0960-24
Ref. arch K-HE-0960-HD-24V



K-HE-1440-HD-24V
K-HEHD-1440-24
Ref. arch K-HE-1440-HD-24V



K-HE-1920-HD-24V
K-HEHD-1920-24
Ref. arch K-HE-1920-HD-24V


RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT



K-1530-RGB+W-24V
K-RGBW-1530-24
Ref. arch K-1530-RGB+W-24V



K-1920-120-RGB-24V
K-RGB-1920-120-24
Ref. arch K-1920-120-RGB-24V



WP-K-1920-120-RGB-24V
KWP-1920-120-RGB-24
Ref. arch WP-K-1920-120-RGB-24V



K-RGB-1200-24V
K-RGB-1200-24
Ref. arch K-RGB-1200-24V



K-RGB-0700-24V
K-RGB-700-24V
Ref. arch K-RGB-0700-24V


RELATED ACCESSORIES > RELATED LED > WHITE MONO



WP-K-1640-HD-IP65-24V
KWP-GHD-1640-24
Ref. arch WP-K-1640-HD-IP65-24V




WP-K-1220-IP65-24V
KWP-1220-IP65-24
Ref. arch WP-K-1220-IP65-24V



K-0480-24V
K-0480-24
Ref. arch K-0480-24V



K-0960-24V
K-0960-24
Ref. arch K-0960-24V



K-1440-24V
K-1440-24
Ref. arch K-1440-24V