

# Profile PDS-UST

Ref. A02725

Ref. arch C2725



- Mounting to 16 mm | 0.63" drywall
- No collision with the ceiling structure
- Stable mounting to a suspended ceiling
- Non visible aluminum elements

## APPLICATION

- main and decorative lighting


## MOUNTING

- in drywall, with screws
- can be easily connected into runs and systems

## ADDITIONAL INFORMATION

- smooth transition from a recessed into a suspended fixture
- in order to protect the lighting fixture during installation, a TECH-KA protective insert should be used
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING



## TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver non anodized
Possible fixture IP	20
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	52.2 mm
Height	19 mm
LED gluing width A	14 mm
Number of LED strips A (8 mm wide)	1
Possibility of obtaining a line of light	yes
Building type	Commercial, HoReCa object, Retail, Residential, Entertainment/ Arts, Outdoor
Facility zone	office, communication routes and corridors, lobby / foyer, conference room
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Mounting to drywall	yes

Length	Ref
1000 mm	A02725N_1 C2725NA_1
2005 mm	A02725N_2 C2725NA_2
3010 mm	A02725N_3 C2725NA_3

# Profile PDS-UST

Ref. A02725

Ref. arch C2725

To cover with plaster	yes
Wire out back of extrusion	yes

## SAMPLE PROJECTS



## RELATED PROFILES > UNIVERSAL



### PDS-ZM-PLUS

A02056

Ref. arch C2056

# Profile PDS-UST

Ref. A02725

Ref. arch C2725

## RELATED ACCESSORIES > RELATED COVERS

NAME	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
LENSO <span style="background-color: red; color: white; padding: 2px;">NEW</span>	PC	46.6 %	clear	B17112T 17112
LIGER	PC	70 %	frosted	B17037M 17037
		32 %	black	B17037C 17040
KA-COM	PVC	70 %	frosted	B17179M 17179
		93 %	clear	B17179T 17180
HS	PC	73 %	frosted	B17208M 1369
		94 %	clear	B17208T 1370
KA-PRO	PC	67 %	frosted	B17064M 17064
		94 %	clear	B17064T 17065
KA	PC	63 %	frosted	B17035M 17035
		91 %	clear	B17035T 17036


## RELATED ACCESSORIES > RELATED END CAPS

NAME	MATERIAL	COLOR	REF.
PDS-ZM-PLUS	ABS	gray	C24364C02 24364
		white	C24364C10 24397
		black	C24364C07 24365
		metalized	C24364L01 C24364L01


## RELATED ACCESSORIES > RELATED LED



**8K-WP-K-1210-12V**  
8K-WP-K-1210-12V



**8K-WP-K-1220-12V**  
\_błąd  
Ref. arch 8K-WP-K-1220-12V



**8K-WP-K-1275-12V**  
\_błąd  
Ref. arch 8K-WP-K-1275-12V

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT



**8K-WP-K-1920-120-RGB-24V**

KWP-8KHDRGB-1920-24

Ref. arch 8KWPK1920120RGB24V

---

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER




GLAND

**6x1,2**

C24517C07

Ref. arch 00802

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > TECHNICAL AND PROTECTIVE INSERTS



PROTECTIVE INSERT

**TECH-KA**

C24530C02

Ref. arch 17123