

# Profile TAKO

Ref. A05392

Ref. arch B5392



- Invisible groove edge
- Minimum height

## APPLICATION

- furniture and decorative lighting


## MOUNTING

- recessed, with mounting adhesive or double-sided adhesive tape

## ADDITIONAL INFORMATION

- cover with a simplified structure
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING



## TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver anodized
Possible fixture IP	20
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	27.2 mm
Height	9.1 mm
LED gluing width A	13 mm
Number of LED strips A (8 mm wide)	1
Building type	Residential, Retail, HoReCa object
Facility zone	furniture, shop windows and exhibition
The cover is cut to the length of the profile	yes
Wire out end cap	yes
Wire out back of extrusion	yes

Length	Ref
1000 mm	A05392A_1 B5392ANODA_1
2005 mm	A05392A_2 B5392ANODA_2

# Profile TAKO


Ref. A05392

Ref. arch B5392


## SAMPLE PROJECTS



## RELATED ACCESSORIES > RELATED COVERS

NAME		MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
T		PMMA	83 %	<input type="checkbox"/> frosted	B17015M 17015

## RELATED ACCESSORIES > RELATED END CAPS

NAME		MATERIAL		COLOR	REF.
TAKO EKO		PP		<input type="checkbox"/> white	C20053C10 20053

## RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONNECTORS



CONNECTOR  
**ZD-PION-90**  
C28244N00  
Ref. arch 43504



CONNECTOR  
**ZD-PION-135**  
C28245N00  
Ref. arch 43505

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER



GLAND

**6x1,2**

C24517C07

Ref. arch 00802

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SECURITY AND BLOCKS



BLOCK

**ZD**

C28195N00

Ref. arch 42521

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SPRINGS FOR RECESSED MOUNT AND MOUNTING TRACKS



SPRING

**KDU**

00844V1